

For more information regarding Rx ranges and technical specifications,
please ask your IOT area representative.

Semi-Finished Single Vision (Gray and Brown)								
Material	Diameter (mm)	Base Curve	True Curve (D)	Back Curve (D)	Back Curve Radius (mm)	Front Curve Radius (mm)	CT (mm)	ET (mm)
PLASTIC 1.50 NEOCHROMES® NEOCHROMES® <i>Dark</i>	76	1.25	1.25	6.25	123.832	424.000	12.1	16.2
	76	2.25	2.30	6.25	123.832	230.435	13.3	16.0
	76	3.25	3.27	6.25	123.832	162.080	14.8	16.1
	76	4.25	4.26	6.25	84.800	124.413	10.1	13.0
	76	5.25	5.28	6.25	84.800	100.379	11.7	13.2
	76	6.25	6.25	6.25	84.800	84.800	9.1	9.2
	76	7.25	7.28	6.25	84.800	72.802	10.7	9.2
	76	8.25	8.32	6.25	84.800	63.702	12.7	9.5
POLYCARBONATE NEOCHROMES® NEOCHROMES® <i>Dark</i>	76	0.50	0.54	4.25	124.706	981.481	8.8	14.5
	76	1.25	1.28	4.25	124.706	414.063	9.8	14.6
	76	2.25	2.29	4.25	124.706	231.441	9.9	13.1
	76	3.25	3.29	4.25	124.706	161.094	11.4	13.5
	76	4.25	4.26	6.11	86.743	124.413	10.6	14.0
	76	5.25	5.23	6.11	86.743	101.338	11.5	13.7
	76	6.25	6.29	6.11	86.743	84.261	10.0	10.6
	76	7.25	7.26	9.5	55.789	73.003	8.7	14.0
TRIVEX® NEOCHROMES®	76	8.25	8.28	9.5	55.789	64.010	10.4	13.9
	75	2.00	1.52	5.59	94.78	349.02	12.3	18.0
	75	4.00	3.49	6.99	75.83	151.73	8.3	13.5
	75	5.00	4.47	6.99	75.83	118.48	7.5	11.3
	70	6.00	5.46	6.99	75.83	97.06	5.7	7.7
HI-INDEX 1.60 MR-8 NEOCHROMES®	70	8.00	7.44	8.69	60.97	71.27	7.9	9.8
	73	0.50	0.59	6.39	82.942	898.305	7.5	14.9
	73	1.25	0.95	6.39	82.942	557.895	7.2	14.3
	73	2.25	1.82	6.39	82.942	291.209	9.1	15.1
	73	3.25	3.06	6.39	82.942	173.203	8.3	12.7
	73	4.25	3.97	5.66	93.640	133.501	9.8	12.1
	73	5.25	5.00	5.68	93.310	106.000	9.2	10.0
	73	6.25	5.88	5.66	93.640	90.136	9.3	8.9
	73	7.25	6.96	5.66	93.640	76.149	9.6	7.5
HI-INDEX 1.67 MR-10 NEOCHROMES® NEOCHROMES® <i>Dark</i>	73	8.25	7.92	5.66	93.640	66.919	11.8	8.4
	75	1.00	0.84	8.46	62.648	630.952	5.1	16.2
	75	2.50	2.19	8.46	62.648	242.009	5.2	14.7
	75	4.00	3.52	7.28	72.802	150.568	5.6	11.3
	75	5.00	4.41	7.29	72.702	120.181	6.1	10.7
	75	6.00	5.31	7.29	72.702	99.812	6.7	10.0
	75	7.00	6.20	7.30	72.603	85.484	7.7	9.8
	75	8.00	7.09	7.32	72.404	74.753	10.0	10.5

For more information regarding Rx ranges and technical specifications,
please ask your IOT area representative.

Flat Top 28 (Gray and Brown)									
Material	Diameter (mm)	Base Curve	True Curve (D)	Back Curve (D)	Back Curve Radius (mm)	Front Curve (mm)	CT (mm)	ET (mm)	Add Range
POLYCARBONATE	75	2.25	4.18	4.25	126.794	239.819	9.8	13.1	1.00 - 3.00
	75	4.25	6.12	6.25	86.601	124.413	9.7	13.4	1.00 - 3.00
	75	6.25	6.18	6.25	85.761	84.261	9.8	10.5	1.00 - 3.00
	75	8.25	9.63	9.50	55.036	64.165	8.7	12.3	1.00 - 3.00

NEOCHROMES®

with Camber Technology

This information is not available due to the variable base curve of the Camber lens blank.
Please contact Technical Services for more information about Neochromes Camber lenses.